



CAMERA SYSTEMS






K7000B Gemineye™ 7" LCD Color System

The 7" LCD high-resolution colour monitor included with this system provides the optimal viewing area for mobile CCTV applications. Excellent picture quality is assured even in low-light conditions using a CMOS Colour infrared camera. The flat, widescreen monitor allows unobtrusive mounting with a large, easily viewable screen area. Expandable up to 2 cameras.



FEATURES & BENEFITS

- CMOS 18 LED infrared camera
- Larger 1/3" camera sensor
- Integrated moulded shroud
- Two camera expandable
- Monitor with touch & backlight buttons
- 76H x 592V camera resolution

COMPONENTS

-  M7000B
-  C2013B
-  ECTC20-4 (20m/65')

EXPANSION OPTIONS

-  Any current ECCO camera
-  ECTC5-4 (5m/16'), ECTC10-4 (10m/32'), ECTC20-4 (20m/65')



M7000B

internal controller	Yes
colour	Yes
voltage	12-24
power consumption (W)	5.0
day / night light sensor	Yes
dimensions	174 x 114 x 24
weight	399g
temperature (C°)	-20 to +70
screen size	7.0"
mirror image	Yes
sunshade	Yes
max cameras	2
4 pin camera connection	Yes



C2013B

colour	Yes
power consumption (W)	1.0
day / night light sensor	Yes
dimensions	79 x 81 x 50 mm
weight	272g
temperature (C°)	-30 to +70
lens angle	75° Horizontal 170° Vertical
lens size	1/3"
infrared LEDs	18
mechanical vibration	8G
4 pin camera connection	Yes (threaded connection)

WIRING GUIDE

